

Waterproof LED Downlight

Description:

DLW Recessed IP65 Waterproof LED Downlight is required for zone regions near water sources. completed lamps IP65 waterproof protection with waterproof driver and waterproof connectors . it makes the room look better and they will have a higher resistance to steams.This downlights finish paint by Anti-Corrosive materials and fully water-resistant which means they are the perfect option for outdoor LED downlights , round and square types for option

It is Ideal for for your planned retrofit or new constructing,Creating tremendous energy saving at a extremely affordable price



Application:

- Villa ,Lobbies, Corridors
- Bathroom Lighting Restaurant
- Residential Lighting



Information:

Features:

- Completed lamps IP65 Waterproof Protection with waterproof driver and waterproof connectors
- Die-casting ADC12 Aluminum, powder painting, acid and alkali resistance, oxidation resistance.
- 4 kind of colors reflectors for options
- Round and Squares shape optional
- Extremely long lifetime
- Energy savings
- Maintenance savings
- instant light-up
- Excellent light quality
- No UV or IR radiation
- Environmentally-friendly: no mercury
- Medium useful life > 50,000 hours (L80B50) at ambient temperature of 25 °C

Specification:

- Power supply : IP65 Waterproof BOKE Driver
- Lighting Source: OSRAM BRIDGELUX
- Housing material: aluminum.
- Housing color: White Black
- Working environment temperature: -20oc ~ +45oc.
- Lamp Certificates: CE ROHS



Model No.	Input voltage(V)	Power (w)	LED Chip	Luminous flux (lm) (±5%)	Beam angle(o)	CCT (K)	CRI	Size (mm)	Cutout
OP-DLW15W W4 R	AC220-240V AC100-277V	15W	OSRAM Bridgelux	1500lm	15/24° 38/60°	2700K 3000K 4000K 5000K	90+	Φ100*H64mm	ø90mm
OP-DLW25W W4 R	AC220-240V AC100-277V	25W	OSRAM Bridgelux	2500lm	15/24° 38/60°	2700K 3000K 4000K 5000K	90+	Φ136*H83mm	ø125mm
OP-DLW35W W4 R	AC220-240V AC100-277V	35W	OSRAM Bridgelux	3500lm	15/24° 38/60°	2700K 3000K 4000K 5000K	90+	Φ159*H96mm	ø145mm
OP-DLW45W W4 R	AC220-240V AC100-277V	45W	OSRAM Bridgelux	4500lm	15/24° 38/60°	2700K 3000K 4000K 5000K	90+	Φ180*H109mm	ø165mm
OP-DLW15W W4 S	AC220-240V AC100-277V	15W	OSRAM Bridgelux	1500lm	15/24° 38/60°	2700K 3000K 4000K 5000K	90+	W100*L100 *H64mm	W90* L90mm
OP-DLW25W W4 S	AC220-240V AC100-277V	25W	OSRAM Bridgelux	2500lm	15/24° 38/60°	2700K 3000K 4000K 5000K	90+	W136*L136mm *H83mm	W125* L125mm
OP-DLW35W W4 S	AC220-240V AC100-277V	35W	OSRAM Bridgelux	3500lm	15/24° 38/60°	2700K 3000K 4000K 5000K	90+	W158*L128mm *H96mm	W145* L145mm
OP-DLW45W W4 S	AC220-240V AC100-277V	45W	OSRAM Bridgelux	4500lm	15/24° 38/60°	2700K 3000K 4000K 5000K	90+	W180*L180mm *H109mm	W165* L165mm



R= Round



S= Square



Pictures :

